



SPECIFICATIONS

Current Rating: 1A AC,DC
Voltage Rating: 125V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 20mΩ Max.
Insulation Resistance: 100MΩ Min.
Withstanding Voltage: 500V AC/minute
Pin Material: Brass/Gold-plated 3u"
Solder Tabs: Brass/Tin-plated
Material: Nylon 6T,UL94V-0
Color: Natural(Beige)

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
A1254WR-S-02P	1.25	7.65	8.07
A1254WR-S-03P	2.50	8.90	9.32
A1254WR-S-04P	3.75	10.15	10.57
A1254WR-S-05P	5.00	11.40	11.82
A1254WR-S-06P	6.25	12.65	13.07
A1254WR-S-07P	7.50	13.90	14.32
A1254WR-S-08P	8.75	15.15	15.57
A1254WR-S-09P	10.00	16.40	16.82
A1254WR-S-10P	11.25	17.65	18.07
A1254WR-S-11P	12.50	18.90	19.32
A1254WR-S-12P	13.75	20.15	20.57
A1254WR-S-14P	16.25	22.65	23.07
A1254WR-S-15P	17.50	23.90	24.32
A1254WR-S-16P	18.75	25.15	25.57
A1254WR-S-20P	23.75	30.15	30.57
A1254WR-S-30P	36.25	42.65	43.07

深圳市鑫南天科技有限公司

UNIT: mm SCALE: 1 of 2
DRAWN BY: 董正一 APPROVED BY: 董正一
2001.02.01 2001.02.01

1.25mm PITCH
90° WAFER-SMT TYPE
ULTRA LOW PROFILE

REV.	DESCRIPTION	DATE	GENERAL TOLERANCE	ANGLE±	DRAW NO.:	REV.:
B2	REVISE	2006.07.04	X.X±0.25		A1254WR-S-IP	B2
B1	REVISE	2006.08.01	X.XX±0.15			
B0	NEW RELEASE	2005.12.08	X.XXX±0.05			