



1. 材料
 - A. 主体: LCP, 黑色, 白色, UL 94-V0;
 - B. 端子: 铜合金, 电镀铜金;
 - C. 外壳: 不锈钢, 镀金镍;
2. 主要特性
 - A. 电压等级: 20V AC;
 - B. 电流: 3A;
 - C. 工作温度: -40°C~85°C;
3. 电气要求:
 - A. 接触电阻: 40mΩ Max. (初始), 50mΩ Max. (最后);
 - B. 电压: 100V AC 1分钟;
 - C. 绝缘电阻: 100MΩ min. DC 500V;
4. 机械性能:
 - A. 插入力: 5~20N。(共1~10,000次);
 - B. 拔出力: 8~20N。(共1~1,000次);
 - C. 耐久性寿命: 5,000次;

PIN	SIGNAL NAME	PIN	SIGNAL NAME
A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND

REV	日期	变更说明	变更人
XNT			

图号 (PART NO):	XNT-1608-01	品名 (TITLE):	TYPE-C-16P沉板0.80
料号 (NUMBER):	X.XX ±0.20	JEFF	核维 (APPD):
客户 (CLIENT):	X.XXX ±0.15	AG	设计 (DRA):
		COCO	绘图 (DIB):
			日期 (DATE):
			2017-04-06
			单位 (UNITS):
			MM
			比例 (SO):
			1/1
			英寸 (INCH):
			1
			REV
			A



深圳市鑫南天科技有限公司
Shenzhen XinNanTian Technology Co., Ltd

These drawing and specifications are the property of XNT. All rights reserved. No part of this document may be copied or used in any manner without the prior written consent of XNT.

Autodesk 教育版产品制作