


**ELECTRICAL**  
 VOLTAGE RATING: 20V DC (R.M.S)  
 CURRENT RATING: 10A  
 CONTACT RESISTANCE: 30mΩ MAX.  
 INSULATION RESISTANCE: 100 MΩ MIN.  
 DIELECTRIC WITHSTAND VOLTAGE: 500V AC (R.A.M)  
 TEMPERATURE RANGE: -25°C TO +85°C  
 MATERIALS & PLATING: SEE THE TABLE BELOW.

REV.	ECN NO.	DESCRIPTION	DESIGN	DATE
A		INITIAL	Lucky	2018.11.30

规格	料号
针芯 2.5	XNT-DCJJB0050-25
针芯 2.0	XNT-DCJJB0050-20



UNLESS OTHERWISE SPECIFIED TOLERANCES



深圳市鑫南天科技有限公司  
 Shen zhen Xin Nan Tian Technology Co., Ltd

DECIMALS: ANGLES:



PART NAME: DC POWER JACK 2.0/2.5

ITEM	NAME	QTY	DESCRIPTION	NOTE
6	GROUND	1	STAINLESS STEEL;	T=0.15
5	SHELL	1	IRON, NICKEL PLATING OVERALL	T=0.4
4	TERMINAL 3#	1	STAINLESS STEEL;	T=0.3
3	TERMINAL 2#	1	BRASS; SILVER PLATING OVERALL	
2	TERMINAL 1#	1	COPPER ALLOY; Cu-Sn PLATING OVERALL	T=0.3
1	HOUSING	1	PA9T; COLOR BLACK	
0		1		

DWG NO.	DESIGN:	CHECK:	APPROVED	PART NO.	REV.	UNIT:	SHEET:
	Lucky		Lucky	XNT-DCJJB0050-25/XNT-DCJJB0050-20	A	mm	1/1